

# SPECKTRON

## DKS2-55 AP

55" Digital Kiosk



- Capacitive multi-touch interactive display
- Freestanding slim design
- Protective glass fascia & built-in speakers
- 55" Ultra HD Portrait Display
- Integrated Android system
- Supports superior video content & applications



4K

ULTRA  
HD



SLIM

SLEEK  
DESIGN



USB  
CONNECTIVITY



MULTI  
TOUCH



RETAIL



LEISURE



HOSPITALITY



HEALTHCARE



GOVERNMENT



MALLS



AIRPORTS

# DKS2-55 AP



Specktron's 55" Digital Kiosk is the ideal solution for a variety of environments, such as hospitality, retail, airports & public spaces. Featuring Ultra HD resolution, 178°/178° wide-angle viewing, 450-nit brightness, 5000:1 contrast ratio, 24/7 operation, capacitive touch to deliver messages with vivid clarity in a sleek, slim design. Photo and video files can be played back using the in built Android system and 16GB of internal memory.

## SPECIFICATIONS

PANEL		MAINBOARD FEATURES	
Panel Size	55"	Operating system	Android 7.1.2
Max-Resolution(H x W)	2160 x 3840	CPU	2 x A72 cores + 2 x A53 cores
Viewing angle	178°	Memory	4 GB
Display colors	16.7 M	Storage	16 GB
Brightness	450 cd/m <sup>2</sup>	Internet connection	Wi-Fi and LAN
Contrast ratio	5000:1	SD Card Support	Yes
Response time	5ms	Google Play Support	Yes
Display model	9:16	Scheduled On/ Off Power	Yes
24/7 Operation	Yes	Inputs	HDMI-IN x 1, VGA-IN x 1, USB 3.0 x 2, USB 2.0 x 1, TF Card x 1
Speakers	2 x 5W	Outputs	HDMI-OUT x 1
TOUCH		CMS	Supports pushing content and remote management of unit
Touch frame	PCAP		
Touch points	10		
MEDIA FORMATS		PRODUCT DIMENSIONS	
Video format	AVI(H.264, DIVX, DIVX, XVID), rm, rmvb, MKV(H.264, DIVX, DIVX, XVID), WMV, MOV, MP4(H.264, MPEG, DIVX, XVID), DAT(VCD format), VOB(DVD format), FMP, MPEG, MPG, FLV(H.263, H.264), ASF, TS, TP, 3GP, MPG	Dimensions	1961 x 778 x 450 mm
		Weight	53 kg
Audio format	MP3, WMA, MP2, OGG, AAC, M4A, MA4, FLAC, APE, 3GP, WAV.	Operating temperature	0°C-50°C
Picture format	BMP/PNG/GIF/JPEG	Operating humidity	10%-90%
Text format	PDF, WORD, PPT, TXT, EXCEL	Storage temperature	-20°C-60°C
		Storage humidity	10%-90%
POWER			
Power Supply	AC 100-240V 50 /60 HZ		
Power Consumption	180W		
Standby	<5W		

\*Model subject to availability in your region.